

Attorney Docket Number 20010389.ORI

Septic System Treatment Process

Inventor: Michael J. Jungbauer

Background of the Invention

Field of the Invention

This invention relates to septic systems and more specifically to a process for waste treatment, for preventing system failures, and for rejuvenating failed systems.

Description of the Related Art

In septic systems, there are frequently failures of the system resulting in water backups into homes and businesses, or insufficient treatment of the waste materials resulting in pollution of the area around the septic tanks, or drain fields, and potential runoffs which may damage ecosystems, streams, rivers, and nearby properties.

Failures of septic systems occur for a variety of reasons, including, overloading the septic tank with grease, fats and oils, which overburden the system. The septic system effectiveness may be reduced by the use of soaps, antibiotics, or chemicals which kill the organisms intended to biologically break down the waste materials in the septic system. The septic tank may also contain too high of a concentration of organic solids which can clog the septic tank.

The septic system may fail due to lack of oxygen in the septic tank, or in the drain field, or both. The organisms that break down the organic materials in the septic system need oxygen to thrive. If the organism population is reduced by lack of oxygen, cleaning chemicals, antibacterial soaps, medications, or other chemicals, the system can fail due to

1 such organisms, the drain field and surrounding soils may become compressed and
2 impermeable, or an overdeveloped biomat may develop, causing a backup of waste into
3 the household or business, or a surfacing of the waste above the drain field and
4 consequent run off and pollution.

5 A process of treating wastes in a septic system is needed which will restore
6 unhealthy or blocked septic systems and keep septic systems healthy to protect the
7 system from breakdowns and protect the environment.

8 9 Summary of the Invention

10
11 The septic system treatment process restores and maintains septic systems by
12 keeping the organisms in the system healthy from one end of the system to the other.

13 Oxygen is added to the septic tank to ensure the organisms therein are not oxygen
14 starved. Oxygen is also added to the drain field to make sure that the organisms therein
15 are not oxygen starved, thus preventing an over developed biomat. Healthy populations
16 of organisms which feed on organic waste will keep the system functioning, eliminating
17 backups and ensuring proper waste treatment to protect the environment.

18 If needed, organisms can be added to the populations in the system to get the
19 system back to normal operation. Chemicals may also be added to liberate oxygen from
20 materials in the system. Enzymes may also be used to stimulate biological activity.

21 The process provides an inexpensive remedy for failed septic systems and a
22 reliable waste system for households and commercial properties.

23 24 Objects of the Invention

25
26 It is an object of the invention to prevent backups of wastewater septic systems.

27 It is an object of the invention to keep wastewater septic systems healthy and in
28 operation.

It is an object of the invention to prevent over developed biomas in unhealthy wastewater septic

It is an object of the invention to prevent pollution of the environment by septic system failure.

1 It is an object of the invention to provide a remedy for home and commercial-
2 sized septic systems.

3 It is an object of the invention to reduce the cost of restoring a septic system to
4 health.

5 Other objects, advantages and novel features of the present invention will become
6 apparent from the following description of the preferred embodiments when considered
7 in conjunction with the accompanying drawings.

8
9 Brief Description of the Drawings

10
11 The figure is a schematic showing the septic system.

12
13 Description of the Preferred Embodiments

14
15 Referring to the Figure, in a typical household, a pipe 30 carries the wastes 35
16 mixed with water from the household 10 to the septic system 20. The septic system 20
17 comprises at least one septic tank 32 (or multiple septic tanks, aerobic tank, or cesspool),
18 and a drain field 40 adjacent the septic tank 32. Household 10 is a source of waste
19 material 35 from bath tubs 11, bathroom sinks 12, toilets 13, dish washing machines 14,
20 kitchen sinks 15, disposals 16, clothes washing machines 17, and floor drains 18. These
21 sources will deliver to septic system 20 organic wastes from humans in the form of
22 solids, liquids, and toilet paper. The septic tank 32 will also receive grease, fats, oils,
23 ground foodstuffs, soaps, medical wastes, and chemical wastes, which are to be treated
24 by the septic system 20. In commercial settings, other wastes may be added to the system,
25 such as chemical wastes or other biodegradable wastes.

26 The septic tank 32 is equipped with a blower 34 which forces air through a hose
27 36 into an air ring 37 supported by a cylinder 38 in the septic tank 32. The air ring has
28 holes or nozzles 39 therein for mixing air into the waste 35. The air contains oxygen, and

the oxygen is used by the bacteria in the waste 35 to break down the waste into the most favorable form

1 In cases where the septic system does not have a means for adding oxygen into
2 the septic tank 32, an aerator such as shown in the Figure can be added to the septic tank
3 32 by hanging a cylinder 38 supporting a hose 36 and an air ring 37 for adding air to the
4 waste 35. It has been found that when the lack of a healthy population of organisms in the
5 waste 35 is the cause of the failed system, that a combination of adding air, and
6 repopulating the organisms in the tank, can repair the system in as little as 72 hours. The
7 percolation rate in the drainfield area 40 can be increased from zero to 50% in 36 hours,
8 and to a normal percolation rate in 72 hours. The septic tank turbidity is related to the
9 number, position and size of air holes or nozzles 39 used on the air ring 37.

10 *12 -* The effluent waste 35 in the septic tank 32 leaves the tank by way of holes and
11 enters the drain field 40, which has an aggregate rock layer 44 and a top fill layer 42 on
12 the ground 45. The waste 35 is further treated by organisms as it flows through the drain
13 field 40. The drain field 40 should also have access to oxygen to keep the organism
14 population at a healthy level. The organisms living in the drain field 40 help keep the
15 drain field open by keeping the top fill 40, dirt and soil in the aggregate rock 44, and
16 ground 45, from clumping up and blocking the flow of waste 35, in order to prevent
17 backups into the septic tank 32, and into the household 10.

18 Oxygen is added to the drain field 40 by use of aerators 60, which bring air from
19 above the surface of the top fill 42 to the aggregate rock layer 44. The number of aerators
20 60 needed is proportional to the amount of oxygen needed to supply the waste with
21 oxygen to keep the organism population at effective levels for cleaning the waste and
22 breaking down the biomat. A typical drain field 40 for use in a normal household 10
23 would have six aerators 60 in the drain field 40. The aerators 60 can be added to an
24 existing drain field 40 by augering a six inch diameter hole down to the aggregate rock 44
25 level and placing an aerator therein. Similarly, aerators 60 can be installed while
26 constructing a new drain field 40.

27 When a drain field does not have a healthy population of organisms, the top fill 42
28 may become compacted or depressed, as shown by sink 50, indicating that the ground
29 that the top fill 42 is on is too hard to pass the lack of organisms keeping the top fill 42

1 Another factor affecting the drain field 40 is rain. Rainwater competes with the
2 flow of waste 35, and rainwater may have a pH which changes the health of the organism
3 community. In addition, fertilizers, herbicides, pesticides and other chemicals can also
4 reduce the organism population. Without a good percolation rate in the drain field the
5 effluent will not flow and may come to the surface or back up the system into the
6 household. A surface back up will then run off, causing pollution.

7 In systems that have failed, tests in the drain field and in the septic tank may
8 indicate the cause of the system failure. When the cause is a reduced population of
9 organisms, more organisms may be introduced, along with enzymes, or chemicals known
10 to increase the populations of the organisms in the system.

11 *OK* The organisms used in septic systems are a combination of microbes and bacteria,
12 that break down, or fractionalize, or degrade the organic and inorganic materials in the
13 septic tanks and drain fields. Enzymes may also be used to enhance the biological activity
14 in the waste effluent.

15 *OK* Sometimes nutrients such as molasses, sugar, or potassium, are added to the septic
16 system to encourage organism growth. Other growth promoting additives include forms
17 of oxygen-liberating substances, such as hydrogen peroxide, potassium carbonate, and
18 sodium percarbonate, and *biological* bio-surfactants or other surfactants, all available commercially.

19 Drain fields may fail due to *biological* biological Oxygen Demand (OD) levels, total
20 suspended solids levels, and fat, oil, and grease levels. These failures may be corrected by
21 increasing the dissolved oxygen levels in the septic tank to between 5 and 6 mg/l.

22 Obviously, many modifications and variations of the present invention are
23 possible in light of the above teachings. It is therefore to be understood that, within the
24 scope of the appended claims, the invention may be practiced otherwise than as
25 specifically described.

26 What is claimed is: